

Sign Types

The **DISABLED PARKING PERMIT sign (Rb-93)**

must be used to exempt vehicles displaying a valid a Disabled Persons Parking Permit from parking prohibitions at designated parking spaces, and thereby to indicate parking spaces designated for use by disabled persons possessing a valid Disabled Persons Parking Permit.

The **DISABLED STANDING EXEMPTION sign (Rb-94)** must be used to exempt vehicles displaying a valid Disabled Persons Parking Permit from standing prohibitions.

The **DISABLED STOPPING EXEMPTION sign (Rb-95)** must be used to exempt vehicles displaying a valid Disabled Persons Parking Permit from stopping prohibitions.

Guidelines For Use

Disabled parking control exemption signs may be augmented, but not replaced, by pavement markings.

When multiple parking stalls are to be designated with the Rb-93 sign, each parking stall must have an individual sign.

Location Criteria

For parallel parking stalls:

- The DISABLED PARKING PERMIT sign must be placed adjacent to the stall within its longitudinal limits;
- The sign placement must clearly indicate which stall the sign applies to;

- The sign must not interfere with passengers entering or leaving the vehicle; and
- The sign should be mounted at a height of 2 m to 3 m, measured from the top of the curb to the bottom of the sign.

For angle parking or parking perpendicular to the roadway:

- The DISABLED PARKING PERMIT sign must be placed at the side of the road, midway between the lateral limits of the stall; and
- The sign should be mounted at a height of 1.5 m to 2.5 m, measured from the top of the curb to the bottom of the sign.

Legal Status

Highway Traffic Act, Regulation 581 (R.R.O. 1990).

Signs are also enforceable in municipalities by municipal by-law.

Minimum Sheeting Requirement

Type I

Special Considerations

N/A